



LIGHTING FOREVER


Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209-3SYGSURC/S530-A3

■ Features :

- Two chips are matched for uniform light output, wide viewing angle
- Long life-solid state reliability
- I.C. compatible/Low power consumption
- Pb free
- The product itself will remain within RoHS compliant version



■ Descriptions :


- The 209LED lamp contain two integral chips and is available as both bicolor and bipolar types.
- The Brilliant Yellow Green and Red light is emitted by diodes of AlGaInP and AlGaInP
- Type of bipolar lamps are both White Diffused and Color Diffused while the bicolor are White Clear

■ Applications :

- TV set
- Monitor
- Telephone
- Computer

PART NO.	Chip		Lens Color
	Material	Emitted Color	
209-3SYGSURC/S530-A3	AlGaInP	Brilliant Yellow Green	White Clear
	AlGaInP	Brilliant Red	

Package Dimensions



Notes: 1. All dimensions are in millimetres

- 2. An epoxy meniscus may extend about 1.5mm(0.059") down to the lead.
- 3. Tolerances unless Dimension $\pm 0.25\text{mm}$.

Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit	
Forward Current	IF	SYG/S530	25	mA
		SUR/S530	25	
Operating Temperature	Topr	-40 to +85	°C	
Storage Temperature	Tstg	-40 to +100	°C	
Soldering Temperature	Tsol	260	°C	
Electrostatic Discharge	ESD	SYG/S530	2000	V
		SUR/S530	2000	
Power Dissipation	Pd	SYG/S530	60	mW
		SUR/S530	60	
Reverse Voltage	VR	5	V	

Note: *1:IFP Conditions --Pulse Width $\leq 1\text{msec}$ and Duty $\leq 1/10$.

*2:Soldering time ≤ 5 seconds.



LIGHTING FOREVER

Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209-3SYGSURC/S530-A3

Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition	
Luminous Intensity	I _v	SYG/S530	100	200	/	mcd	I _F = 20 mA
		SUR/S530	160	320	/		
Viewing Angle	2θ 1/2	/	20	/	deg	I _F = 20 mA	
Peak Wavelength	λ _p	SYG/S530	/	575	/	nm	I _F = 20 mA
		SUR/S530	/	632	/		
Dominant Wavelength	λ _d	SYG/S530	/	573	/	nm	I _F = 20 mA
		SUR/S530	/	624	/		
Spectrum Radiation Bandwidth	Δλ	SYG/S530	/	20	/	nm	I _F = 20 mA
		SUR/S530	/	20	/		
Forward Voltage	V _F	SYG/S530	/	2.0	2.4	V	I _F = 20 mA
		SUR/S530	/	2.0	2.4		
Reverse Current	I _R	SYG/S530	/	/	10	μA	V _R = 5 V
		SUR/S530	/	/	10		









LIGHTING FOREVER

Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209-3SYGSURC/S530-A3

Typical Electro-Optical Characteristic Curves:





LIGHTING FOREVER







Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209-3SYGSURC/S530-A3

Typical Electro-Optical Characteristic Curves:

(SUR)





LIGHTING FOREVER

Technical Data Sheet

3.0mm Multi-Color Round Type LED Lamps

209-3SYGSURC/S530-A3

■ Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	10 SEC	76 PCS	0/1
2	Temperature Cycle	H : +100°C 15min ∩ 5 min L : -40°C 15min	300 CYCLES	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∩ 10 sec L : -10°C 5min	300 CYCLES	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -40°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	TEMP : 25°C IF = 20mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C / 85% RH	1000 HRS	76 PCS	0/1



LIGHTING FOREVER

Technical Data Sheet


3.0mm Multi-Color Round Type LED Lamps

209-3SYGSURC/S530-A3

Packing Quantity Specification

1. 500PCS/1Bag, 6Bags/1Box
2. 10Boxes/1Carton

Label Form Specification



- CPN: Customer's Production Number
- P/N : Production Number
- QTY: Packing Quantity
- CAT: Ranks
- HUE: Peak Wavelength
- REF: Reference
- LOT No: Lot Number

Notes

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.

EVERLIGHT ELECTRONICS CO., LTD.

Tel: 886-2-2267-2000, 2267-9936

Office: No 25, Lane 76, Sec 3, Chung Yang Rd,

Fax: 886-2267-6244, 2267-6189, 2267-6306

Tucheng Tainpei 236 Taiwan R.O.C

<http://www.everlight.com>